Certificate of Location of Government Corner

ID#: 621209 **Description:** SEC CEN 12 62 **Date Set:** **County:** Olmsted

Section: 12 **Township:** 106N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

6-4-1875 T. Hunter P. 281 No. 278, stake set at true inters. Lines with line set for fencing south. 1/16 south set stake 20.08 1/4 M & L N1°W for line west run out for fencing N 89°E 1/16 west set stake 19.91 1/2 M & L N 88 3/4 E 1314.4

4-16-1979 County Surveyor dug at the 1/16th South of the Center 12. Found a stake hole down about 20" from the surface. Set a 1/2" diam. Bolt (1" sq. head) with Rt. Angle bend at bottom. Bolt about 12" long (head to bend) - also set a piece of limestone on North side of bolt. Corner falls 2' West of corner fence post of fences N-E-W and came .8'N and 1.64' West of the Traverse nail (removed).

4-16-1979 County Surveyor dug on the S.W. side of three corner post complex at the Center 12 at near comp. Loc (comp. At intersection of E-W 1/4 line and line from the N 1/4 Cor. 12 to the stake hole fd. At the 1/16th So. of the Center 12. Did not find anything. Base of fence comes part of fence. South would be within a few inches of the comp. Location - set a wood stake about 1 1/2" sq. x 2' long (up 6"0 at 1.0' West and 1.0' South of the traverse nail (removed) - after computing in office of location of 1/16th corner South (fd stake hole). This wood stake at Center 12 is now ±.3' too far North and ±.25' too far East to hit corrected computed location.

4-16-1976 County Surveyor set traverse point at the 1/16th East between two corner posts at the 1/16th East of Center 12.

12-30-1997 Roger Brand & Associates used computed center at intersecting quarter lines.