Certificate of Location of Government Corner

ID#: 621306 **Description:** 1/4 SEC COR 13 14 62 **Date Set:** 8/24/2004 **County:** Olmsted

Section: 13 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

Post with Mn/DOT witness sign 1' south
3/4" iron pin S 17.54'
This corner is located by GPS measurement

Corner History:

9-1853 Set by William Jones 40.00 Set gr. Section post deposited charred stake. Made mound trench & pits & planted Br. Oak acorns NE & SW; plum seeds SE & NW
51.50? Brook 10 lks wide runs East & enter dry bottom.)

9-1891 T. Fraser P. 454 Sec. 14 found indication of old stake - set boulder stone

6-30-1964 J. Kerr found a boulder stone 16" under ground by fence corner. Set a permanent marker of a Cast Iron Monument over boulder 1/2" x 10" steel on east and west sides of boulder.

1965 J. Kerr checked corner. Frost had heaved it nearly out or kids. Removed boulder set iron rod below with CIM well below ground - lands black & sticky. Details B 90 P 13 bottom page. J.Kerr

12-4-2003 Mn/DOT survey crew found CIM with top broken off 0.5' below surface.

8-24-2004 County Surveyor found broken CIM down 0.5' leaning slightly south. Removed broken CIM and found 1/2" rerod down 1.6' in good condition. Set 7' telspar pipe w/cast iron cap at surface over 1/2" rerod. Post with Mn/DOT witness sign 1' south.

3-20-2007 County Surveyor found telspar pipe w/CIC up 0.1' in good condition.