Certificate of Location of Government Corner

ID#: 621504 **Description:** 1/4 SEC COR 15 22 62 **Date Set:** 9/5/1973 **County:** Olmsted

Section: 15 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of E-W twp road and 45' east of centerline of field entrance north
Bottle cap in W side PP #15834 SSE 36.33'
Bottle cap in N side PP #15833 WSW 101.27'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes West between sections 15 and 22. 40.05 chs. Set post at quarter section corner. Deposited charred stake, made mound, trench, and pits and planted cherry seeds NW and SE.

11-1856 Thomas Hunter (P. 18 No. 29), County Surveyor, used corner to sub-divide section 22. Meas. South to center 22 39.71 N 25' W 1/16th West 19.97 1/2 N 89° 55' E 1318.35 1/16 East 19.85 1/2 S 89° 55' E 1310.43 BT - S 53°E 130 lks S 72°W 56 1/2 lks.

8-7-1968 J. Kerr Meas from CIM at SE 15 West, found fence south at 1316.9, set short rod at 2632. Rod lies 4' north to north edge traveled road. 46' west to center east rail - 24' to centr tele bell which lies 3' west of north - meas. West sec 15-16-21-22 Con't west to rod set centerline N-S roads 4' south of N edge traveled road. Set rod at 5270 or 2638 from rod set at S 1/4 15 East of 1/4 15-22 from CIM SE 15 2632

9-5-1973 County Surveyor found short iron set 8-7-1968 2632' west of CIM at 14-15-22-23. Dug carefully and found original Gov't wood charred stake down 3' in clean soils. Set 16" piece of cast sled shoe from bob sled with glass broken around iron orig. stake in such good shape preserved for office dry lag. Set CIM over corner below - stake 1.25 W of 1968 iron.

9-22-2006 Yaggy Colby Associates found CIM in good condition.

3-28-2008 Roger Brand & Asscociates found CIM in good condition.

4-3-2009 County Surveyor found CIM down 0.6' in good condition.