Certificate of Location of Government Corner

ID#: 621506 **Description:** 1/4 SEC COR 15 16 62 **Date Set:** 4/10/2009 **County:** Olmsted

Section: 15 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 3' west of centerline of N-S twp road and in line with fence west
CP of cemetery east 33'
This corner is located by GPS measurement

Corner History:

9-1853 Set by William Jones 6.89 Br. Oak 8 in. diam. 40.00 Set post at gr. Sec. corner. Br. Oak 4N 10E 45 Br. Oak 6S 25W 80

8-1891 Thos Fraser P. 453 No. 437 Found stake set by Hunter 50 lks west of NW corner cemetery. Set stake and smal stone by side of old stake.

8-1898 W. Fraser P 640 No. 576 Found stake and small stone set by T. Hunter (?) Bearing 1/4 line west N 89° 40 W.

8-8-1968 J. Kerr found limestone as recorded. Set permanent marker of Cast Iron Monument over stone and steel rod.

3-16-2005 Yaggy Colby Associates used CIM for survey in NW 1/4 section 15.

9-22-2006 Yaggy Colby Associates used CIM in large survey of section 10 and 15.

3-28-2008 Roger Brand & Associates found CIM in good condition 1.3' deep.

4-10-2009 County Surveyor found 3/4" pipe down 0.3' in good condition. Removed pipe and found CIM down 1.2' in good condition. Removed CIM and found 1" x 9" x 14" stone w/iron on west side down 2.8' in good condition. Removed stone and iron and set 5' telspar pipe with Cast Iron Cap down 0.4' at CIM position.