Certificate of Location of Government Corner

ID#: 621604 **Description:** 1/4 SEC COR 16 21 62 **Date Set:** 8/7/1973 **County:** Olmsted

Section: 16 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' north of centerline of E-W twp road and in line with fence south
Bottle cap in W side PP #15812 S 80.9'
28" Oak N 39.5'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes West between sections 16 and 21. 3.40 Brook 5 lks wide runs North 40.00 chs. Set quarter section post Burr Oak 4 in. N61 1/2 E 16 lks. Burr Oak 5 in. S621/2 W 118 lks

7-1891 Thomas Fraser (P. 493 No. 467), County Surveyor, found stone set by Hunter in unrecorded survey 1/16 east set boulder 19.97 1/2 M & L 1318.35 B.T. S 22 3/4 E 12" Bl Oak 54 lks.

8-1898 Will Fraser (P.640 No. 576), County Surveyor, found stone. 1/16 west set stone 2 x 8 x 20 M & L 19.90 to sec. Stone. 1/16 center SW 1/4 16 set stone 19.93 M & L N-S 1/16 line N 5' W 1/16th North set stone 2 x 6 x 18 M & L 19.95 1/2 N 10' E

8-7-1968 J Kerr. Meas. from temp iron set at SE corner 16 West - iron as 0.0. Found fence south at 1/16 at 1320.5 R boulder at 1318.35. At 1/4 16-21 found fence south at 2640 R stone at 2636.7 Rod 4' south N edge traveled road surface in line fence south

5-8-1970 County Surveyor ran and meas. Line center 16 over 1/16 stone accurately 65' South west - meas north half direct 1316.75. Proj & meas line south on offset - missed 1/16 cor 65.55 set 1/2" rod at 1316.75. 66.1 east of random. Pulled rod set with 1968 traverse. Corner came slightly east of fence north - just north centerline road maybe 1'±

8-7-1973 County Surveyor dug and found limestone with wood stakes around it. Set a CIM over the stone with a rod beside the stone centering over the top of stone.

4-9-2009 County Surveyor found CIM down 0.5' in good condition.