# Certificate of Location of Government Corner

**ID#:** 621806 **Description:** W 1/4 SEC COR 18 62 **Date Set:** 8/10/2007 **County:** Olmsted

**Section:** 18 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

**Reference Ties:**

The corner falls at edge of woods and 79 1/2' NW of north bank of creek
30d spike recessed 0.1' in W side 18" Black Oak NNW 14.55'
County Survey Disk in NNE side 12" Oak WNW 10.84'
County Survey Disk in SE side 20" Oak SW 46.16'
This corner is located by GPS reference stations "Dam Mist A & B"

**Corner History:**

1853 Gov't Notes John Ball, Deputy Surveyor. North between sections 13 and 18. 40.00 chs. Set post for 1/4 section corner. Burr Oak 10 in. S78W 66 lks. Burr Oak 14 in. S82°E 49 lks 33.97 Burr Oak 14 in. 36.23 Brook 10 lks wide runs NW 40.00 Set quarter post

1-1882 Thomas Hunter, County Surveyor (Book A, Page 372, No. 363, and Old Fieldbook 5, Page 130) "1/4 post missing, but both witness trees still standing, from which we found, by digging, the remains of old stake in the ground.--Set new stake properly marked in its place & drove it well down." He used this corner to set the 1/16 West, a stake, midway (20.03 chs.) and on line to the Center 13, a stake, set at intersecting 1/4 lines.

5-16-1883 T. Hunter (Old Fieldbook 14, page 2) "Ran line from 1/4 post between 18 & 13 on the South and measured line through to C (W. 6-7) = 1 1/2 miles, Distance=119.87--13lks.short. Set temporary stake at D (W.1/4 Cor. 7) 40. S of C and at E (W.7-18) 40. S of D."

6-1893 William Fraser, Deputy County Surveyor, (Book A, Page 512, No. 480) "Found stake as set by Hunter. Tested by witness tree and found correct. Planted stone 18" x 10" x 2"." He used this corner to set the 1/64 East, a stake, on line and midway (9.33chs.) to the 1/16 East, a stake, set on line and according to Gov't measure (West 18.66 chs., East 19.98 chs.) to the Center 18, a stone with stake by its side, set at intersecting 1/4 lines.

10-1930 John Kerr (Kerr Book 4, Page 11-18) measured 2620.5' North from the S.W. Cor. 18 to 2" thick pointed limestone with remains of stake by side. "Replaced stake on S. side of stone and set stake on N. side as well." Original Bearing Tree S71°30'W 43 feet. He used this corner to set the Center 18 at intersecting 1/4 lines. He also set the 1/64 East and the 1/16 North midway (1314.9) and on line to the N.W. Cor. Sec. 18 as set this survey.

1-1973 McGhie and Betts found stone and took new witness trees.

8-18-1981 County Surveyor found limestone with 1/2" rod by its side. Dug out stone and found the remains of stakes on the North and South sides. Set cast iron cap on telspar pipe at stone location.

10-9-2006 County Surveyor found cast iron cap on telspar pipe up 2' bent and leaning.

8-10-2007 County Surveyor removed bent and leaning cast iron cap on telspar pipe and set 5 1/2' telspar pipe w/cast iron cap at surface from GPS and previous traverse data.