Certificate of Location of Government Corner

ID#: 621809 **Description:** SEC CEN 18 62 **Date Set:** **County:** Olmsted

Section: 18 **Township:** 106N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

6-6-1893 W. Fraser P. 512 No. 480 Sec 18. Set stone with marked stake by side at true intersecting lines 1/16 south drove stake 19.90 M & L N 1/4 W 1/16 west drove stake on line and 19.98 west N 89 52 E Set stake at 1/64 corner M & L above 1/16 and W 1/4 18 at 9.33 for line south (from W 1/4 18) Then 1/16 stake at 1231.56 then 19.98 to center stone set 1318.68 (total 2550.24)

10-1930 J. Kerr Book 4 Page 10 Sec. 18 Set stone 3 x 10 x 22 and stake intersecting lines
16" white oak S40°E 20.7 12" white oak N 88 ? 27.75 Measure of N-S 1/4 line 5254.0 (positive measure) Measure West to W 1/4 18 2545.9 (questionable believed correct) Set 1/64 corner 612.9' east of W 1/4 18. No description 1/16 North set stone at 1316.5 1/64 north set stake at 656.8 as 1/2 way point Set corner 1/64 612.9 east of W 1/4 18 after continuing line only to E 1/4 18 Evidently 2633.0' N to N 1/4 18 - 2621' S to S 1/4 18

8-20-1981 County Surveyor calculated location of Kerr's Center 18 and also Kerr's tie to White Oak believed to be Kerr's NW bearing tree would put his corner about 2' over the West edge of ditch washed 8'+ deep. Found stone of exact Kerr dimension 6' East of this location and at the bottom of the ditch. We dug on the E-W 1/4 line from edge of bank West but 1'+ of sand over natural soil and did not have time to dig thoroughly. We did, however, find the base of a small port or possible stake beneath the sand and extending 1 1/2' into soil. This point 2.3' S and 2.0' E of t.n. Kerr's center calculation 1.77' South and 8.76' East of t.n

8-25-1981 County Surveyor dug on E-W 1/4 line from a point 3' East of the t.n. East for 3' to 4' to the edge of ditch. Dug off top 1 1/2' of sand to get to natural soil. Found hole of 2" to 3" diameter running down 2' with about 6" circle of sand around it most of the way. Probe dropped in to hilt but no wood at all. Took ties: Spike in Elm NE 2.7'; Spike in Cut of Elm NW 6.87'.

12-30-1987 Yaggy Colby used computed center at intersecting quarter for survey of Chester Woods Park boundary.

4-9-2002 GGG, Inc. did a survey in the south half of Section 18 and shows on the certificate of survey that a monument was found.

7-5-2013 County survey crew searched the area but did not find a monument. The area is in a steep, eroded ravine.