Certificate of Location of Government Corner

ID#: 622009 **Description:** SEC CEN 20 62 **Date Set:** **County:** Olmsted

Section: 20 **Township:** 106N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

5-26-1882 T. Hunter P.377 No.368 set stake at true inters lines. 1/16 east set stake M&L 19.92-1/2 N89° 27' W. 1/16 west set stake with stone on S side M&L 19.97-1/4 N89° 27' W. 1/16 north set stake M&L 19.97 to 1/4 cor stone 2x10x22. 1/16 center NW 1/4 20 set stake inters lines no meas.

4-22-1971 County Surveyor meas from nail in near center of N-S road at 1/4 20-21, found large anchor post in E-W fence line at 1311.0, con't meas on fence line west, found area of 3 large corner posts, large steel post anchoring new fences south and west, large wood post anchoring fence east leaning some east and between and slightly north remains of fallen corner post of very old fence north which came about 2629.5 from .00 nail. Found large limestones south and west of steel corner post. Set to hold post and smaller vertical limestone just west of old post of fence north, could have been placed as corner in place of stake but would come almost exact record 2630 from road center line. Drove 3/8"x4' electric fence post deep by stone. Accepted as corner until proven otherwise. Did not look for 1/16 stone west or 1/4 corner east as road filled at least 6' with culvert in place no more than 8" north. Drove rod in center road in line fence east as recorded until dug up. Corner likely not ther in draw.

7-17-2000 GGG reports rod at center 20 gone. County Surveyor told them to use intersecting quarter lines.