Certificate of Location of Government Corner

ID#: 622404 **Description:** 1/4 SEC COR 24 25 62 **Date Set:** 7/16/2003 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 1' north of centerline of E-W twp road
Pk nail in NW side Power Pole ENE 138.59
Pk nail in East side wood corner post, North 44.74
5/8" pipe North 32.61
Pk nail in top of lone wood post in R/W fence SSW 40.79
This corner is located by GPS reference stations "Whitcomb A & B"

Corner History:

10-17-1853 Gov't Notes. W.A. Jones, Deputy Surveyor, set post 39.87 chs. West of Sec. Cor.

6-27-2001 County Surveyor dug with backhoe to cover lost position which falls in line of fence bulkhead north and in centerline of E-W road. We dug through 3 road surfaces and hit bedrock at 8' deep, found no corner in poor conditions. We will set corner M&L after digging settles.

6-21-2002 Brand & Massey Surveying Inc. set 5/8" pipe w/cap #26371 at County Surveyor position.

7-16-2003 County Surveyor found 5/8" pipe down 0.2'. Took local ties and removed. Set CIC on a 4.0' telspar pipe down 0.4'.

3-21-2007 County Surveyor found telspar pipe w/CIC down 0.4' in good condition.