Certificate of Location of Government Corner

ID#: 622406 **Description:** 1/4 SEC COR 23 24 62 **Date Set:** 9/7/1973 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' west of centerline of N-S twp road and 15' south of centerline of field entrance east
Punch hole in N end 18" CMP NNE 39.43'
Punch hole in S end 18" CMP E 28.62'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes North between sections 23 and 24. 40.00 chs. Set quarter section post. Deposited charcoal stake. Made mound, trench, and pits and planted Burr Oak acorns N.E. and S.W. cherry seeds S.E. and N. W. 47.60 chs. Brook 5 lks wide runs east.

7-1871 Thomas Hunter (P. 186 No. 197), County Surveyor, found old stake by fence corner.

8-1887 Hunter (P. 421 No. 410) found part of stake deep in center of the road in line with fence east. Set stone by stake. Set 1/16 stone west midway and on line.

9-7-1973 County Surveyor set corner on projected line from Center 23 found and 1/16 stone found and doubled the measure. Dug the area but found nothing. Set C.I.M. over a 16" rod.

4-28-2000 County Surveyor found CIM down 0.6' in good condition.

6-8-2001 County Surveyor found CIM down 0.6' in good condition.