Certificate of Location of Government Corner

ID#: 622504 **Description:** 1/4 SEC COR 25 36 62 **Date Set:** 10/31/1995 **County:** Olmsted

Section: 25 **Township:** 106N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 3 1/2' north of centerline of CR 129 and 1' east of fences north and south
Punch mark in N end 30" RCP SE 72.09'
Punch mark in S end 30" RCP NE 68.57'
Ref pipe SSW 43.92'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes W.A. Jones, Deputy Surveyor West on true line between sections 25 and 36. 40.00 chs. Set post at quarter section corner. Deposited handfull of gravel. Made mound, trench, and pits.

Found no other records of this corner.

10-6-1975 County Surveyor dug 8' x 8' x 5' deep at midway and on line location but found nothing.

10-16-1975 County Surveyor set CIM over 1/2" x 18" iron rod as corner midway and on line betwen Sec. corner 25-26-35-36 and East Sec. corner 25-36.

6-19-1995 County Surveyor found CIM set P.K. at surface. Set 1" square pipe w/cap ± 40' south centerline CR 129 and 5' west of fence line south. Angle at Ref. pipe, angle RT old blue Eyota water tank to 1/4 corner 25-36 28° 21' 17" to 1/4 corner 25-36 VA 84° 06' 31" dv 08 slope 44.15 Hor 43.915.

10-31-1995 county highway department set 1" square pipe w/cap at surface from 1995 overlay tie out.

4-24-2009 County Surveyor found 1" square pipe w/cap at surface in good condition.