Certificate of Location of Government Corner

ID#: 622505 **Description:** SEC COR 25 26 35 36 62 **Date Set:** 10/31/1995 **County:** Olmsted

Section: 25 **Township:** 106N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 7 1/2' north of centerline of CR 129, 7' west of centerline of old twp road north and 4' west of centerline of old twp road south
County Survey Disk in SE side PP #1753 ENE 52.18'
Punch mark in N end 36" RCP NE 68.45'
Punch mark in S end 36" RCP SE 71.46'
Punch mark in S end 36" RCP SW 30.63'
Punch mark in N end 36" RCP NW 19.34'
Ref pipe NNW 55.80'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes W.A. Jones, Deputy Surveyor North between sections 45 and 36. 80.00 chs. Set post corner to Sections 25, 26, 35, and 36. Deposited handful of white flint. Made mound, trench, and pits and planted cherry seeds SW and NE.

4-1863 P.C. Compton P.68 No.96 shows sec corner (see survey for breakdown of sec 35).

6-1913 Dave William's (P. 224B), County Surveyor, found 4' x 3' x 2' boulder in center of crossroads with spot underneath stone very evident as stake remains.

1949 county highway department (Book 165 P. 1) found pointed boulder.

10-3-1975 County Surveyor dug with backhoe in CR 129 and found huge boulder 4' deep. Boulder had 6" x 6" flat spot on top with a depression in the center. Set scrap iron over stone, junk around stone, and CIM over all.

6-19-1995 County Surveyor found CIM. Set 1" square pipe w/cap on W edge abandoned road north of CR 129. Centerline road east 9', centerline CR 129 south 64'. Angle at Ref. pipe, angle Rt P.K. in PP #1752 (2nd pole east on N side CR 129) to sec corner 82° 51' 37.5" to sec corner 25-26-35-36 (CIM 8-1/2' N of centerline CR 129) VA 89° 32' 25" dv 07 slope 55.80 Hor 55.80.

10-31-1995 county highway department set 1" square pipe w/cap at surface from 1995 overlay tie out.

4-24-2009 County Surveyor found 1" square pipe w/cap at surface in good condition.