Certificate of Location of Government Corner

ID#: 622804 **Description:** 1/4 SEC COR 28 33 62 **Date Set:** 4/24/2009 **County:** Olmsted

Section: 28 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in centerline of CR 129 and 48' east of centerline of field entrance south
Spike in 15" Oak S 80'
County highway disk in PP WSW 197.5'
Center 6" Pine tree SSE 41.5'
This corner is located by GPS measurement

Corner History:

10-17-1853 Gov't Notes West on true line between sections 28 and 33. Var. 9° 34' E. 39.89-1/2 set post at gr. section corner, deposited charred stake. 79.79 to section corner.

5-1856 Thos Hunter P.6 No.9 shows 1/4 post. 1/16 east 19.82 chs M&L to sec corner. Meas 39.86 chs south to center sec.

4-1863 P.C. Compton P.69 No.97 shows 1/4 stake used to set center sec 28. 1/16 north set, no meas.

7-1939 J. Kerr P.488B S.28-29-32-33 town board found boulder meas west 2629.22', east 2622.3' referenced.

6-30-1964 J. Kerr found 1/2" pipe over boulder. Placed permanent marker of a Cast Iron Monument over 3/4" x 15" steel rod.

5-30-2001 Roger Brand found CIM with top broken off. Set drag tooth over remaining monument.

4-24-2009 County Surveyor found drag tooth down 0.4' in good condition. Removed drag tooth and found CIM without head down 1.1' in good condition. Removed CIM and found 3/4" rerod down 2.6' in good condition. Removed 3/4" rerod and set 3.4' telspar pipe w/Cast Iron Cap down 0.4' at CIM position.