Certificate of Location of Government Corner

ID#: 622805 **Description:** SEC COR 28 29 32 33 62 **Date Set:** 6/30/1964 **County:** Olmsted

Section: 28 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Moument

Reference Ties:

The corner falls 4' east of centerline of CR 129 south and 2' south of centerline of CR 129 east
State Reference Point in SE side PP #43005 SW 44.45'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes William A. Jones, Deputy Surveyor Set post at corner to sections 28, 29, 32, and 33. 80 chs. Erected mound with trench and pits.

4-1863 P.C. Compton (P 69 No. 97) used section corner to set 1/16 corner North.

7-1939 John Kerr for Town Board (P 488 B), set 1" Iron Shaft as corner after lengthy fieldwork and record searching.

11-1961 M.H.D. crew dug down and found nothing. Stone said to be destroyed by grading. Measured down from quarter corner to C/L of East-West road going East 2638.32', and placed a Spike. No Ties.

6-10-1964 John Kerr, County Surveyor, found Pipe set in 1939. Set CIM over 1" Iron.

3-10-1997 Gerald Stephas, Mn/DOT Survey Crew Chief, recovered the 1964 Cast Iron Monument, updated the topography and measured new reference ties.

For details and survey analysis, contact the Minnesota Department of Transportation Surveys Office in Rochester, Minnesota.

4-15-2009 County Surveyor found CIM down 0.8' in good condition.