Certificate of Location of Government Corner

ID#: 622806 **Description:** 1/4 SEC COR 28 29 62 **Date Set:** 6/30/1964 **County:** Olmsted

Section: 28 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 112' north of centerline of WBL of FAI-90 and 23 1/2' south of north FAI-90 R/W fence
Post w/sign 2' north
This corner is located by GPS measurement

Corner History:

Reference: History is of record at the Olmsted County Surveys Office indexed as Document No. 622806.

10-1853 Gov't Notes William A. Jones, Deputy Surveyor. Set post at quarter corner to sections 28 and 29. 40. Chs. Erected mound with trench and pits.

4-1863 P.C. Compton (P 69 No. 97) used Stake to set center corner section 28.

7-1939 John Kerr for Town Board (P. 488 B), found original stake hole running thru clay to shell rock. Set 1" pipe with bridge bolt riser.

11-1961 M.H.D. crew (road is in cut at this point) dug hole 4.5' down, found northern. Measured down from NE section corner (which was found) to fence line at quarter corner 2640'. Used East-West fence line and C/L road to set 3/4" Iron Pin.

6-30-1964 John Kerr, County Surveyor, found the 1939 3/4" x 20" bolt in 1" x 30" pipe. Found Iron Pin in C/L of road (assumed set by M.H.D.) and removed the same. Set a Cast Iron Monument over 3/4" x 20" bolt. Corner lies 2.0' East of West edge of traveled road, lines fences East-West.

7-30-1968 John Kerr found CIM, set new reference ties.

6-16-1978 County Surveyor found CIM 15' North of North I-90 R/W fence and 8' West of C/L of old road running North.

4-11-1997 Gerald Stephas, MN/DOT Survey Crew Chief, recovered the 1964 Cast Iron Monument, updated the topography and measured new reference ties.

For details and survey analysis, contact the Minnesota Department of Transportation Surveys Office in Rochester, Minnesota.

4-9-2009 County Surveyor found CIM down 0.2' in good condition. Set post w/sign.