Certificate of Location of Government Corner

ID#: 622904 **Description:** 1/4 SEC COR 29 32 62 **Date Set:** 7/27/1978 **County:** Olmsted

Section: 29 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The monument is at the surface
The corner falls in line with the north-south fence and 19' north of projected east-west fence
Post with sign, south 2'
This corner is located by GPS measurement

Corner History:

9-1853 Gov't Notes. William A. Jones, Deputy Surveyor. West on true line between sections 29 and 32. 39.95 chs. Set post at quarter section corner. Deposited handful of charcoal. Made mound, trench, and pits. Planted cherry seeds N.E. and S.W. 79.90 chs. To section corner.

4-1856 Road Survey by E.P. Bircher, Surveyor, and Thomas Hunter, Deputy, between Sections 29 and 32.

11-1856 Thomas Hunter, County Surveyor, (Book A P. 17 No. 28) used the corner to set the Center 29.

5-1890 Thomas Fraser, County Surveyor, (Book A P. 442 No. 428) could not find this corner to use to set Sec. Cor. 29-30-31-32.

7-1939 John Kerr (Kerr Book 15 P. 125), County Surveyor, could not find this corner to use to set Sec. Cor. 28-29-32-33. The corner comes in an abandoned road.

7-1973 The County Surveyor dug at the Center 32 and found a stake.

7-24&27-1978 The County Surveyor dug with the backhoe in line with the fences North and South and in the center of the old road. Did not find anything. Set a Cast Iron Cap on a 5' square pipe in line with the fences North and South and at double the measure from the stake found at the Center 32 in 1973 over the 1/16th fence North, a property line since before 1875. We projected the line from the N. 1/4 Cor. 29 over the N-S fence at the Center 29 and the N-S fence at the 1/16th South of the Center 29 and the line came at the N-S fence line at 1/4 Cor. 29-32. We also projected the line fromthe fence North at the S. 1/4 Cor. 32 over the stake at the Center 32 and this line also fell on the N-S fence line at 1/4 Cor. 29-32. The corner is 2 1/2' North of the center of the old road.

Reference: History is of record at the Olmsted County Surveys Office indexed as Document No. 622904. Certificate of Location of Gov't Corner filed by Roger W. Brand, dated 8-31-1979.

4-22-1997 Gerald Stephas, Mn/DOT Survey Crew Chief, recovered the 1978 Cast Iron Cap on Square Pipe, updated the topography and measured new reference ties.

For details and survey analysis, contact the Minnesota Department of Transportation Surveys Office in Rochester, Minnesota.

10-14-2010 County survey crew found CIC in good condition