Certificate of Location of Government Corner

ID#: 623005 **Description:** W SEC COR 30 31 62 **Date Set:** 11/9/2006 **County:** Olmsted

Section: 30 **Township:** 106N **Range:** 12W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 2 1/2' north of centerline of E-W twp road, in line with fence south and 70' west of centerline of residential driveway north
County highway disk in PP #15515 NE 40.42'
County Survey Disk in PP #50424 SE 33.04'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: Ball, deputy surveyor. North between 31 and 36. 80.00 set post and drove charred stake.

3-1878 T. Hunter P.332 No.326 found old stake remains in center road. Set stone in place 20x8x3/12. 1/16 east set stone 4x4x20 line shorts govt meas 19 lks. Set stone at 18.92 then 19.93 to S 1/4 30 (a corner found) no notations on N-S sec line.

5-1890 Thos Fraser P.442 No.428. found stone P.332 set by Hunter. Meas south 39.98-3/4 N40'W to stone set M&L.

4-1892 W. Fraser P.475 No.452. found stone set by Hunter. Meas west 39.98 M&L temp stake set.

4-25-1929 J. Kerr Book 1 P.27 first found stone, meas 2 miles west 10540'

1935 MHD found stone 4"x4" top 4"x12" bottom 18" long limestone. RP's: T.P. NW 25.0'. Corner post S30.5'. Gate post NE 65.0'

7-7-1965 J. Kerr found stone badly shattered but large. Set CIM over stone.

10-2-2006 County Surveyor found CIM with head broken off down 1.2' in good condition.

11-6-2006 County Surveyor removed CIM without head and found 3/4" pipe down 2.7' in good condition. Removed 3/4" pipe.

11-9-2006 County Surveyor set 1" square pipe w/cap at surface.