Certificate of Location of Government Corner

ID#: 623209 **Description:** SEC CEN 32 62 **Date Set:** 7/13/2007 **County:** Olmsted

Section: 32 **Township:** 106N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" pipe w/cap RLS #14888

Reference Ties:

The corner falls 1' south of centerline of E-W twp road and 9 1/2' west of fences north and south
This corner is located by GPS measurement

Corner History:

No known records

7-18-1973 County Surveyor found 11 foot (offset) lath set south if true E-W 1/4 line ran from stone and CIM at 1/4 31-32 and iron set M&L at 1/4 32-33. Removed entire road with Wharton Cat and found small wood going down into soft sandy fine sub soil this stake came 10.25 from 11' offset and about 1' + east of fences N and S accepted as corner at least until proven otherwise. S 1/4 set M&L and don't match anything or any fences in area N or S. N 1/4 no record in abandoned road and never set but meas by J. Kerr in 1930's. Set 2x2 wood hub and trash as corner. Set 1/2"x20" + iron 70' north on E side fence row 1' + and 120d 70' south 1' + E of fence running S on transit line road being graded.

7-13-2007 V. Fangman set 1/2" pipe w/cap RLS #14888 at intersecting quarter lines as center section 32.

4-3-2009 County Surveyor found 1/2" pipe w/cap RLS #14888 down 0.1' in good condition.