Certificate of Location of Government Corner

ID#: 623309 **Description:** SEC CEN 33 62 **Date Set:** **County:** Olmsted

Section: 33 **Township:** 106N **Range:** 12W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

5-16-1856 Thos Hunter P.6 No.9 shows center sec 1/16 east 19.92-1/2 M&L to 1/4 post. Meas north 39.86 chs to 1/4 post. T. Hunter ran the N-S 1/16 line in the NE 1/4 but gives no measure.

8-29-1856 T. Hunter P.16 No.25 used or set corner. Meas east 39.85 2630.1 N89-1/2E. 1/16 west 20.07 M&L 1324.62 N89-1/2E. 1/16 south 19.92 M&L 131472 N1010'W. 1/16 center SW 1/4 33 19.92 N to 1/16 N1-1/4°W 19.96 W to 1/16 N89-3/4°E. 1/16 center SE 1/4 33 19.96 W to 1/16 N89° 25' E 19.96 S to 1/16 N1° 5' W.

8-5-1968 J. Kerr meas line from nail in line center roads east and south at 1/4 33-34 set nail in line fences north and south 2638 Hunters record 2630 from center 33 fences west to 1/16 fence south 1325.2 Hunters record 1324.6. From center 33 fences west to nail in center north south roads meas 2626 record 2649.2. From center 33 fences east to 1/16 fence south 1322 record 1315. From center 33 fences east to 1/16 fence north 1317 record 1315. From 1/16 fence east of center 33 which runs north to nail east 1321 record 1315.

3-26-2001 Wayne Claassen used computed center at intersecting quarter lines.

8-23-2002 Brand & Massey Surveying Inc. used computed center at intersecting quarter lines.