Certificate of Location of Government Corner

ID#: 623406 **Description:** 1/4 SEC COR 33 34 62 **Date Set:** 5/31/1973 **County:** Olmsted

Section: 34 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 5' south of centerline of twp road east, 4' east of centerline of twp road south and 28' NW of centerline of twp road on curve
SW corner old concrete culv headwall N 71.95'
SE corner old concrete culv headwall NNE 70.32'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes North between sections 33 and 34. 40.00 chs. Set post at quarter section corner. Deposited charred stake, made mound, trench and pits, and planted cherry seeds SW and NE.

8-1856 Thomas Hunter (P. 16 No. 25), County Surveyor, used corner.

4-1863 Compton (P. 68 Book A), County Surveyor, has "stone" written by corner.

8-5-1968 J. Kerr meas from NE south to nail placed in meas from west of 5270 from CIM SE 32. Meas to centerline rail road 422.9 in centerline existing road. Set 20d nail at 2632 in centerline roads east and south. RP: Nail 46.5 to center top corner post SE, 45.3 to center tele pole NE (Hunters record to NE 33 2630.1). Meas west for 1 mile 1/16 fence north 1321.0 to 1/16 fence south 1316.0 (Hunters record 1315) to 1/4 center 33 fence north and south 2638.0 (Hunters record 2630) RP: Nail insouth edge of north track in old road 8.33 to NW edge with culv headwall. 14.9 to Sw edge south culv headwall. To 1/16 west of center fence south 3963.2 (record 3954.6) to nail in center N-S road at 1/4 32-33 5264 (record 5279.24).

5-31-1973 County Surveyor dug and found boulder 6" x 6" x 16". Drove a 4' piece of steel fence post on the south side of the stone and set a CIM over all.

4-20-2009 County Surveyor found CIM down 1.2' in good condition.