Certificate of Location of Government Corner

ID#: 623505 **Description:** S SEC COR 34 35 62 **Date Set:** 7/20/2000 **County:** Olmsted

Section: 35 **Township:** 106N **Range:** 12W **Monument Description:** 5/8" copper plug w/punch mark

Reference Ties:

The corner falls in centerline of CSAH 7 and 2' north of centerline of twp road east
Ref pipe E 77.20'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes John Ball, Deputy Surveyor, set a corner post 80.00 chains west of S Sec. corner 35-36.

5-1902 William Fraser (P. 14B), County Surveyor, found stake and 9" x 12" x 30" stone. Measured north to the quarter corner 34-35 and then to Sec. corner 26-27-34-35, the quarter corner being on line but not midway.

10-1923 county highway department (B.41 P. 17) found stone in the center of the road.

1957 county highway department (B.214 P. 5) found a limestone and set a 3/4" drill steel rod in place.

1966 county highway department (B. 317) found a steel rod in place.

8-27-1974 County Surveyor set a nail in the pavement using County Highway Department ties for location.

11-21-1974 County Surveyor replaced nail with 1 1/4" x 12" lead pipe set flush with concrete.

5-16-1997 County Surveyor found 1-1/4" pipe in good condition in centerline CR 7.

5-23-1997 County Surveyor set 1" ref pipe.

6-25-1999 County Surveyor tied out corner.

7-20-2000 County Surveyor set 5/8" copper plug w/punch mark at surface from 1999 tie out.

4-24-2009 County Surveyor found 5/8" copper plug w/punch mark at surface in good condition.