Certificate of Location of Government Corner

ID#: 623506 **Description:** 1/4 SEC COR 34 35 62 **Date Set:** 7/21/2000 **County:** Olmsted

Section: 35 **Township:** 106N **Range:** 12W **Monument Description:** 5/8" copper plug w/punch mark

Reference Ties:

The corner falls in centerline of CSAH 7 and in centerline of E-W twp road
Punch hole in top lug bolt N end 24" CMP WNW 62.07'
Punch hole in top lug bolt S End 24" CMP WSW 56.52'
Ref pipe W 151.39'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes W.A. Jones, Deputy Surveyor, set post 40.00 chs. North of S Sec. corner 34-35.

5-1902 William Fraser (P14B), County Surveyor, found boulder stone. Measured north to NE corner Sec. 34 and south to SE corner Sec. 34.

8-27-1974 County Surveyor measured mile from NE Sec. corner 34 to SE Sec. corner 34 and set a small punch hole at this corner on William Fraser's prorated measure.

11-21-1974 County Surveyor set a 1 1/4" x 12" lead pipe at this corner.

5-16-1997 County Surveyor found 1-1/4" pipe in good condition 0.2' W centerline CR 7.

5-23-1997 County Surveyor set ref pipe.

6-25-1999 County Surveyor tied out corner.

7-21-2000 County Surveyor set 5/8" copper plug w/punch mark at surface from 1999 tie out.

4-24-2009 County Surveyor found 5/8" copper plug w/punch mark at surface in good condition.