Certificate of Location of Government Corner

ID#: 623605 **Description:** S SEC COR 35 36 62 **Date Set:** 4/28/1981 **County:** Olmsted

Section: 36 **Township:** 106N **Range:** 12W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 35' north of top of deep cut for E-W road and in line with fence south
County Survey Disk in SW side blazed 11" Burr Oak N50ºW 8.79'
County Survey Disk in SE side blazed 7" Burr Oak N54ºE 25.52'
County Survey Disk in SW side blazed 11" Burr Oak S32ºE 26.60'
Post w/sign 1' north
This corner is located by GPS reference stations "MMR A & B"

Corner History:

1853 Gov't Notes John Ball, Deputy Surveyor West between Sections 1 and 36. 80.00 chs. Set post for corner to Secs. 1, 2, 34 & 36. Black Oak 10 in. S2ºW 235 lks. Burr Oak 14 in. N53ºW 105 lks. Burr Oak 6 in. S70ºE 80 lks. Burr Oak 11 in. N59ºE 34 lks. Found no other records of this corner.

10-1975 County Surveyor measured from the SE corner 36 to the SW corner 35. A Mr. Willey, a farmer who owns land in the NE 1/4 Sec. 2, 105-12, says a Mr. Benedict (1956 plat book shows a Benedict used to own land in the NE 1/4 Sec. 1, 105-12) told him he dug up a stone section corner here but Mr. Willey did not know where.

4-28-1981 County Surveyor set a telspar pipe with Cast Iron Cap as the corner midway and on line between the S 1/4 corner 35 (set this survey) and the S 1/4 corner 36 (set in 1975).

4-27-2009 County Surveyor found cast iron cap on telspar pipe up 0.2' in good condition.