Certificate of Location of Government Corner

ID#: 630104 **Description:** 1/4 SEC COR 1 12 63 **Date Set:** 11/9/2006 **County:** Olmsted

Section: 01 **Township:** 106N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls 1' north of centerline of E-W twp road, in line with fences north and south and 17 1/2' west of centerline of residential driveway north
County Survey Disk in PP SE 50.62'
County Survey Disk in PP NE 45.16'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes William A. Jones, Deputy Surveyor West on true line between sections 1 and 12. 40.025 chs. Set quarter section post deposited charcoal and made mound trench, and pits.

12-1910 Charles Larson County Surveyor (p. 142 Book 8) found 1/4 corner boulder of 1-12.

6-1962 John Kerr County Surveyor (book 85 p 45) at 1/4 corner 1-12 dug and could find no corner set iron midway an online between section corners.

5-1964 John Kerr County Surveyor set C.I.M. over iron set in 1962 at 1/4 corner 1-12.

11-5-1970 County Surveyor dug for C. Larsen stone by hand at 1/4 corner 1-12 found nothing. Reset C.I.M. midway and on line, after resetting east section corner 1-12 (found stone).

7-8-1982 County Surveyor dug at 1/4 corner 1-12 North and west of C.I.M. found pointed boulder 5" x 9" base 11" high standing on crushed rock road which lays right on clay bus soil. So stone must have been set later after road was built.

5-12-1987 County Surveyor dug again at 1/4 corner 1-12 to cover line of fences north and south, conditions poor, found nothing.

6-16-1987 County Surveyor set C.I.M. by occupation. In line of fences north and south and centerline of east-west road. RPs-C.S. in S.E. side of Easter'ly gate post N.E. 39.21', Center line 125 st. N.E. C.S.D. in N.E. side of P.P. # 21429 S.E. 44.12'.

9-22-2006 County Surveyor found CIM without head down 1.1' in good condition.

11-6-2006 County Surveyor removed CIM without head and found 1/2" rerod down 2.1' in good condition.

11-9-2006 County Surveyor set 1" square pipe w/cap at surface.