Certificate of Location of Government Corner

ID#: 630206 **Description:** 1/4 SEC COR 2 3 63 **Date Set:** 4/29/1982 **County:** Olmsted

Section: 02 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 2 1/2' west of N-S fence and 1 1/2' north of E-W fence
County Survey Disk in SE side brace post WSW 6.75'
Post w/sign 1' south
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes: William A. Jones, Deputy Surveyor S9'E on true line between sections 2 and 3. 39.83 chs. Set post at quarter section corner. Deposited charcoal, made mound, trench, and pits and planted cherry seed NE and SW. 79.83 chs to section corner.

6-1857 John B. Fellows, Surveyor, (Book A, pg 26, no. 42) may have used the corner to set the Center 2. Measured north 39.90 chs and east 40 chs.

10-1882 Thomas Hunter, County Surveyor, (Book A, pg380, No. 371) Found stone planted at H (1/4 cor. 2-3) for 1/4 post with part of the original 1/4 post by its side and the remainder lying on the ground near it; mound and pits filled up. He set a stake not marked eleven chains west and on line to a stake found at the Center 3. He also set a stake not marked 11.00 chains east of the stake found at the Center 3 and on line to 1/4 cor. 2-3.

4-28-1982 County Surveyor dug at the corner post to fences N-S-E-W for corner. Found a 1 1/2"x9"x15" limestone standing with edges east and west 2 1/2' west and 1 1/2' north of the corner post. Dug 11.0 chanins west of the stone for Hunter's property corner stake , but didn't find it. Also dug at the Center 3 and 11.0 chns east of the Center 3 but didn't find Hunter's stakes ther either.

4-29-1982 County Surveyor accepted the stone found 4-28-1982 as the corner and drove a square (telspar) pipe with Cast Iron Cap at the location it stood. Dug the stone down on the east side of the pipe. Measured south 2637.19 to section corner 2-3-10-11 and 2628.26 north to north section corner 2-3.

10-19-2006 County Surveyor found cast iron cap on telspar pipe up 0.2' in good condition. Set post w/sign.