Certificate of Location of Government Corner

ID#: 630405 **Description:** SEC COR 4 5 8 9 63 **Date Set:** 3/13/89 **County:** Olmsted

Section: 04 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in centerline of CR 144 west and 1 1/2' east of centerline of CR 144 north
County highway disk in PP #18956 NW 57.22'
County highway disk in PP #18264 SW 51.39'
County Survey Disk in PP #18957 NE 62.06'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones, Deputy Surveyor; North 80.0 set post at corner. RPs- 12" burr oak N89°E 1045 links, 4" burr oak N84°W 35 links, 7" burr oak S18°W 124 links, 7" burr oak S73°E 85 links.

5-1871 Perry by Hunter, Pg.183 No.194; Corner gone, reset from bearing trees and stump. Meas. South and meas 16 west and set stake.

7-1872 T.Hunter Bk.2 Pg.5-6; Found stake .

1929 J.Kerr Bk.12 Pg.62 set boulder with cross

1939 J.Kerr Bk.12 Pg.62; Found above stone gone. Replaced RPs. Meas. East, set axle shaft. Drove 3/4" bolt in shell rock in place of boulder removed.

1952 J.Kerr Bk.55 Pg.69; Run line west and set 1/2" rod.

1956 J.Kerr Bk.65 Pg.43; Ran 7 Meas. Line NE corner 8 south. Set 1/16 south.

10-25-1963 J. Kerr found iron bolt set from references of 1938. Set CIM at this location. RPs-Northeast 18" oak 107.3 feet, Southeast to Northwest cornerof house 92.35 feet, Nail and disc in power pole Southwest 51.47 feet, Nail and disc in power pole Northwest 57.15 feet, Nail and disc in pole Northeast 61.94 feet.

3-13-1989 County Surveyor found C.I.M. down 19" in blacktop road, set 16" C.I.M. over old C.I.M. RP's County Highway Department disc in P.P. # 18956 NW 57.22. County Highway Department disc in P.P. # 18264 SW 51.39. C.S.D. in P.P. # 18957 NE 62.06.

12-4-2003 County Surveyor found CIM at surface in good condition.

9-17-2007 County Surveyor found CIM down 0.2' in good condition.