Certificate of Location of Government Corner

ID#: 630409 **Description:** SEC CEN 4 63 **Date Set:** 11/27/1972 **County:** Olmsted

Section: 04 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
5/8" rerod

Reference Ties:

The corner falls 1 1/2' east of fence north and in line with E-W PP line
This corner is located by GPS reference stations "Indritz A & B"

Corner History:

4-1-1878 Hunter Pg.333 N0.327; Set stake. At intersecting right lines 16 west set stake, found center RR tracks to be 9.38. NOTE: 6-1969; after resetting N 1/4 4 by known RPs after grading , meas. Above as check found both meas, as near exact as possible.

6-1935 county highway department Bk.75 Pg.8; Meas. East to wooden stake & boulder & west to stone.

7-16-1948 J.Kerr Bk.38 Pg.64; Used corner fence post. Run & Meas. Line west to stone at W 1/4 4. Stone lay at 1316.6. Could be from east or west. Found stone 1316.6.

11-1972 County Surveyor found limestone at N 1/4 4. Reset 5/8"x42" iron at intersecting 1/4 lines. Corner about 18" north & east of fence wires of corner post leaning SE at least 30°.

5-1982 County Surveyor dug for Center 4 and found nothing. Left iron inplace.

3-23-1983 V. Fangman found and used 5/8" rerod.

11-3-1987 Kleinschmidt Surveying found and used 5/8" rerod.

5-25-1989 County Surveyor found 5/8" iron. Used for City of Rochester mapping project survey.

8-1-1990 DNR found and used rerod.

12-4-1990 V. Fangman found and used 5/8" rerod.

4-20-1994 DNR found and used iron rod at center of section 4.

8-1-2000 McGhie & Betts used computed center at intersecting quarter lines.

12-1-2003 County Surveyor found 5/8" iron up 1.4' in good condition. Drove 5/8" iron down to surface.