Certificate of Location of Government Corner

ID#: 630509 **Description:** SEC CEN 5 63 **Date Set:** 6/7/2000 **County:** Olmsted

Section: 05 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Intersecting lines of concrete nails N-S-W-E

Reference Ties:

Plastic disc in PP NW 58.12'
Pk nail in S end 30" CMP SE 65.70'
Pk nail in N end 30" CMP SE 44.15'
Ref pipe ESE 103.88'
This corner is located by GPS reference stations "Ref Pipe 630509 & VBC"

Corner History:

10-25-1963 J. Kerr set CIM in place of 1-1/2" pipe used many years as center of section.

? CIM removed in sewer construction. City reference 50' east of the center, by City Engineer.

10-18-1978 County Surveyor removed C.I.M. which was set by the city of Rochester at 50' East. Removed C.I.M. before grading on this road. Set 1/2" iron rods 19.93 East and 69.93 East of the 50' Ref. Monument. The rods are on the So. Side of the East West fence.

8-5-1988 V. Fangman set chiseled marks on manhole ring

8-31-1994 Mn/DOT found and used chiseled mark straddles on manhole ring at center of section 5.

12-24-1994 McGhie & Betts used computed center for East Ridge Subdivision

3-1-1999 City of Rochester survey crew found chisel marks plain on M.H. ring.

5-3-1999 County Surveyor found chisel marks on MH ring. Set ref pipe and tied out corner.

6-7-2000 County Surveyor set concrete nails N-S-W-E for intersecting lines to establish position.

7-19-2001 Land Consultants found and used monument

12-17-2008 GGG Surveying found and used monument

3-10-2009 Yaggy Colby found and used intersecting lines of concrete nails