Certificate of Location of Government Corner

ID#: 630609 **Description:** SEC CEN 6 63 **Date Set:** **County:** Olmsted

Section: 06 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

Reference Ties:

Corner History:

6-10-1856 Thomas Hunter, (Book A, Page 10, Survey No. 16) set stake at intersecting quarter lines. 1/16 South set stake midway and on line at 20.10 chains (1326.60') to South 1/4. 1/16th Center of SE 1/4 set stake at intersecting sixteenth lines.

6-3-1896 William Fraser, County Surveyor, (Book A, Page 603, Survey No. 548) set stake at intersecting quarter lines. RPs - 3" Jack Oak N8°E 5-1/2 links (3.63'), 8" Jack Oak S15-1/2°E 5-1/2 links (3.63'). 1/16th South found remains of old stake and set stake midway and on line at 20.07-1/2 chains (1324.95') to South 1/4. 1/16th East set stake midway and on line at 19.85 chains (1310.10') to East 1/4. Set witness stake at edge of brush 10 links (6.60') east.

1974 Jack Rother reports 1" iron set by McGhie & Betts in college property survey to be gone.

10-13-1976 WHKS used computed center at intersecting quarter lines for the plat of Campustown Subdivision.

6-19-1989 County Survey Crew looked for iron at computed center. Found nothing but hubs, old and new, set by RCC civil technology students.

1-23-2001 McGhie & Betts, Inc. used computed center at intersecting quarter lines.

4-1-2004 MnDNR used computed center at intersecting quarter lines.

8-22-2016 WSB used computed center at intersecting quarter lines.