Certificate of Location of Government Corner

ID#: 630805 **Description:** SEC COR 7 8 17 18 63 **Date Set:** **County:** Olmsted

Section: 08 **Township:** 106N **Range:** 13W **Monument Description:**

Reference Ties:

The corner falls in centerline of CR 143
Spud in PP NE 30.59'
NE corner of block building NW 129.5'
Punched cross in east gate post substation SE 75.55'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones; 80.0 set section post of corner section 7-8-17-18. RPs- 10" burr oak N77 E261, 7" burr oak N12 W39, 6" burr oak S32 W114, 7" burr oak S 7 1/2 E114.

7-1872 T. Hunter, Field Book #2 Pg.5-6; Found stub of old stake & 2 bearing tree stumps.

4--1898 W.Fraser Pg.622 No.565; Found old stake in center road running down 2'. Also stump remains of SW & SE witness trees. Set stone 5x6x18 beside stake. Bearing tree -4" burr oak N42°E80L.

1941 J. Kerr found corner. RP-NE 36.0 60D red oak SE 62.0.

1947 J. Kerr, 16 east set pipe.

8-1963 J. Kerr set CIM over stone. RPs- spud in pp NE 30.59, NE corner block building NW 129.5, punched cross in east gate post substation SE 75.55.

5-1965 J. Kerr Pg.74 Bk.88; Ties to 1/16 corner east- SE 37.2 disc telephone pole, NE 46.1 disc pp.

4-10-1974 County Surveyor reset a shorty on top of the remains of old monument flush with the surface. Took no additional RPs.

5-1-1989 County Survey Crew found CIM in good condition. Used in City of Rochester mapping project survey.

11-25-2003 County Survey Crew found Cast Iron Monument down 0.5' in good condition and measured its position using GPS.

6-2-2017 County Survey Crew found Cast Iron Monument down 0.4' in good condition and removed prior to bituminous overlay.