Certificate of Location of Government Corner

ID#: 630809 **Description:** SEC CEN 8 63 **Date Set:** 7/23/1964 **County:** Olmsted

Section: 08 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

Nail and hub in blazed 14" Oak SSE 104.78'
Post w/sign 2' north
This corner is located by GPS measurement

Corner History:

5-1-1871 Pg.183 No.194; Set stake. 16 east set stake, 16 west set stake.

1952 J.Kerr Bk.55 Pg.4; iron & pipe stones as corner.

10-24-1956 J.Kerr Bk.65 Pg.44; Ran & measured entire E-W 1/4 line west of center. Set 1/16 corner.

7-23-1964 J. Kerr set CIM over 1/2"x18" rod. Corrected corner. RPs- corner fence post E 0.5, nail in hub in 14" blazed oak SSE 104.78.

1-24-1979 Yaggy Associates found and used CIM at center of section 8.

6-13-1989 County Surveyor found CIM deep next to corner post.

1-26-1990 McGhie & Betts found and used CIM.

12-11-2003 County Surveyor found CIM down 1.6' in good condition. Set post w/sign 2' North.

6-20-2006 Yaggy Colby found and used CIM.