Certificate of Location of Government Corner

ID#: 630906 **Description:** 1/4 SEC COR 8 9 63 **Date Set:** 7/23/1964 **County:** Olmsted

Section: 09 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 12 1/2' west of old N-S fence and 1 1/2' south of old E-W fence lying on the ground
Nail and hub 14" Red Oak WSW 31.07'
County highway disk in PP N 198.65'
Post w/sign 2' west
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones; 40.0 set post at 1/4 section corner, and made trench. RP-13" burr oak N57 E 110.

5-1871 T. Hunter Pg.183 No.194; Corner gone, all evidnece & bearing trees gone. Reset on section line M & L 39.96 1/2, 16 west set stake.

4-1875 T. Hunter Pg.267 No.265; Found stake standing.

1927 J.Kerr Bk.3 Pg.37 scout camp; Set greenish pointer boulder as corner.

7-23-1964 J. Kerr found pointed boulder 1/2" rod by side. RPs-WSW nail and hub 14" red oak 31.07', North nail and disc in power pole 198.65', 1/2" x 48" rod south 0.5' rod above ground 1.5'.

6-1-1989 County Surveyor found CIM in good condition. Set post sign 1.0' West of C.I.M.; old fence laying on the ground 1.5' North. Old N-S fence 12.5' East.

12-15-2003 County Surveyor found CIM at surface in good condition. Set post w/sign 2' West.