Certificate of Location of Government Corner

ID#: 631009 **Description:** SEC CEN 10 63 **Date Set:** 7/23/1964 **County:** Olmsted

Section: 10 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

The corner falls in line with N-S fence and 8 1/2' north of fence west
Center 16" blazed Burr Oak N 64.6'
Center 20" blazed Burr Oak W 44.8'
Center blazed Red Oak SSE 32.8'
Sign in wood fence post 1' north
This corner is located by GPS reference stations "Goodman E & F"

Corner History:

NO RECORDS

8-3-1959 J.Kerr Bk.75 Pg.44; Set 1/2" rod at intersecting quarter lines.

7-23-1964 J. Kerr found 1/2" rod set CIM to preserve corner. RPs- center 16" burr oak blazed N 64.6, center 20" burr oak blazed W 44.8, center red burr oak blazed SSE 32.8, 3/4" rod up 18" E 0.5, corner is in line N-S fences , 2.5' N of E-W fences.

5-31-1979 T. Taylor found and used monument at center of section 10.

7-31-1980 T. Taylor found and used CIM.

8-21-1981 Yaggy Associates found and used CIM.

8-3-1983 McGhie & Betts found and used CIM.

7-15-1986 Land Consultants found and used 5/8" rod.

5-11-1993 Yaggy Colby found and used CIM.

9-22-2006 County Surveyor found CIM down 0.7' in good condition. Set sign in wood fence post.