Certificate of Location of Government Corner

ID#: 631204 **Description:** 1/4 SEC COR 12 13 63 **Date Set:** 10/12/1963 **County:** Olmsted

Section: 12 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls under E-W fence
Center 16" Ash WNW 16.0'
Center 36" Maple NNW 134.5'
Post w/sign 1' north
This corner is located by GPS reference stations "Restoration A & B"

Corner History:

1853 Gov't Notes, William Jones; 39.99 set post of 1/4 section post and made trench. RP- 8" burr oak N58 E176.

1-1882 T. Hunter Pg.372 No.363; Corner gone, bearing trees gone. No evidence or knowledge. Set temp stake for line south.

6-1962 J.Kerr Bk.85 Pg.45; Set 3/4" pipe M & L 2640 to stone found at e 12-13. Meas. North to center 12. 16 north set 1 1/4" pipe.

10-12-1963 J.Kerr found limestone. Set CIM. Center of 16" Ash tree N.77' W. 16.0', Center of 28" Maple tree N.5°W. 128' Center of 36" Maple tree N. 20° W. 1345'.

4-13-1981 County Surveyor found C.I.M. in place and 1963 B.T.'s still o.k.

9-22-2006 County Surveyor found CIM down 0.3' in good condition.