# Certificate of Location of Government Corner

**ID#:** 631209 **Description:** SEC CEN 12 63 **Date Set:** 11/11/1964 **County:** Olmsted

**Section:** 12 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

**Reference Ties:**

The corner falls 10' west of N-S fence and 20 1/2' north of fence west
Center 16" Burr Oak full of fence wires E 8.8'
Center 18" Burr Oak full of fence wires SE 22.5'
Post w/sign 2' east
This corner is located by GPS reference stations "Rubow A & B"

**Corner History:**

1910 C. Larson, Pg.142 B; Set limestone as corner, no desc., 40 chains in all directions.

6-5-1962 J.Kerr Bk.85 Pg.45; 1 1/4" pipe with iron inside with limestones on N & S sides.

11-11-1964 J. Kerr set CIM over 1/2"x10" rod in place of present corner.

9-1-1982 County Surveyor dug for Larson stone (found nothing).

6-5-1987 County Surveyor dug and found a small boulder standing 3.15 east of CIM 10" long.

12-30-1987 Yaggy Colby Associates used computed center at intersecting quarter lines.

10-19-2006 County Surveyor found CIM at surface in good condition. Set post w/sign.