Certificate of Location of Government Corner

ID#: 631309 **Description:** SEC CEN 13 63 **Date Set:** 12/1/1972 **County:** Olmsted

Section: 13 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
1/2" rerod

Reference Ties:

The corner falls 47 1/2' north of centerline of trail
County Survey Disk in SW side CP NW 14.92'
County Survey Disk in N side 11" Oak up 2.3' W 16.18'
30d spike in 14" Black Oak stump SE 31.49'
Post w/sign 2' NE
This corner is located by GPS reference stations "Gator C & D"

Corner History:

1-30-1882 T. Hunter Pg.372 No.363; Set stake. RPs- 4" jack oak S36 3/4E 105 links (69.30'), 4" jack oak S45°W 16 links (10.56'). 16 east set stake.

6-15-1901 R. Fraser Pg.707 No.621; Stake at intersecting 1/4 lines, replace by corner fence post. Tested both B trees. 16 west drove stake, 16 south put stone and stake.

12-1972 T. Ferguson; Set 1/2"x30" rod at intersecting 1/4 lines. RPs-30p spike in 12" black oak NNE 21.75, 30p spike in 10" black oak SE 31.55'.

12-30-1987 Yaggy Colby used computed center at intersecting quarter lines.

10-4-2006 County Surveyor visited area of corner. Found nothing.

11-14-2007 County Surveyor found 1/2" rerod up 0.1' in good condition. Set post w/sign.