Certificate of Location of Government Corner

ID#: 631404 **Description:** 1/4 SEC COR 14 23 63 **Date Set:** 5/28/1965 **County:** Olmsted

Section: 14 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fences N-E-W
Nail in hub in knotty Burr Oak NE 57.1'
Nail in hub in 10" Boxelder WNW 34.75'
Post w/sign 2' east
This corner is located by GPS reference stations "Schmidt E & F"

Corner History:

1853 Gov't Notes: 40.10 set post at 1/4 section corner.RPs- 6" red oak N67 1/2 E189, 6" burr oak S49 E81.

5-1884 T. Hunter Pg.389 No.380; Corner gone and B trees gone. Set stake M&L between section corners and 16 south set stake.

6-1898 W.Fraser Pg.631 No.571; Found stake Pg.389. Set long stone by its side. 16 east set stake.

12-1941 J.Kerr Bk.26 Pg.60; Found stone.

11-1961 J.Kerr Bk.84 Pg.39; Ran & meas. Line from SE 14 west and found corner, set pipe.

5-28-1965 J. Kerr found stone and iron pipe. Set Cast Iron monument over pipe. RPs- nail in hub on triplet boxelders 10" dia. WNW 34.75, nail in hub on knarly topped burr oak NE 57.1.

12-30-1986 County Surveyor found C.I.M., and both trees taken by Kerr in 1965 still standing.

11-15-2007 County Surveyor found CIM down 0.1' in good condition. Set post w/sign 2' E.