Certificate of Location of Government Corner

ID#: 631409 **Description:** SEC CEN 14 63 **Date Set:** 5/28/1965 **County:** Olmsted

Section: 14 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument and 1" Iron Pipe

Reference Ties:

This corner is located by GPS reference stations "Mihm A & B"

Corner History:

11-24-1961 J. Kerr found brass pipe set B26 at 1315.8. Set 1/2" steel rod center at 2632.33 on this line by comp measure. 16 east set at 3950.71. RPs-120d in willow E30.0', spike east side pp NNW 80.7, east side of CR ± 50' by T. Ferguson Oct. 1974.

1962 J. Kerr Bk.85 Pg.36; Measured from CIM to center town road north on N-S 1/4 line approx. 414'.

5-28-1965 J. Kerr Set CIM over rod previously set.

4-25-1975 T. Taylor found and used monument for plat of Fred Schmidt's First Subd.

7-11-1979 T. Taylor found and used monument at center of section 14.

12-30-1986 County Surveyor found CIM in N-S fence line with 1/2" rerod up 2' and fiberglass post up 3' standing beside CIM.

6-12-1988 Roger Brand and Associates found and used CIM.

11-1-1991 Yaggy Colby Associates found and used CIM for plat of Ranch View Subd.

11-4-1993 Land Consultants found and used CIM.

9-22-2006 County survey crew found CIM at surface in good condition.

3-11-2014 Johnson and Schofield Inc. set a 1" pipe with cap at intersecting quarter lines. They note that the CIM falls N 72 degrees 23 minutes 10 seconds East, a distance of 3.10' from the computed center.