Certificate of Location of Government Corner

ID#: 631904 **Description:** 1/4 SEC COR 19 30 63 **Date Set:** 9/1/1978 **County:** Olmsted

Section: 19 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 1' east of fence north and 2' south of fence west
County Survey Disk in CP NE 26.25'
County Survey Disk in CP N 2.80'
This corner is located by GPS measurement

Corner History:

10-1853 Gov't Notes: William A. Jones, Deputy Surveyor East on true line between sections 19 and 20. 38.70 chs. Set post at quarter section corner. Deposited charcoal and made mound, trench, and pits and planted cherry seeds N.E. and S.W.

7-1857 Thomas Hunter (Book A P. 35 No. 56), County Surveyor, possibly used this corner to set the center 30.

Approx. 1955 McGhie and Betts recocrds call for a sickle bar to have been set at the fence corner.

9-1-1978 County Surveyor set a 16" long C.I.M. over a 1/2" x 8" bolt with a 1 1/2" square head at Gov't proportionate measure and on line between the section corners. The corner came less than 1' East of the fence line North and approx. 2' South of the main fence line West. Dug here first and found nothing except on sickle guard which was not set but just lying down about 1' deep.

8-25-1989 County Surveyor found CIM in good condition. Used in City of Rochester mapping project survey.

8-3-2005 County Surveyor found CIM at surface in good condition.