Certificate of Location of Government Corner

ID#: 631906 **Description:** W 1/4 SEC COR 19 63 **Date Set:** 6/25/64 **County:** Olmsted

Section: 19 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 14' east of centerline of field drive north
County Survey Disk in guide post #38690 W 32.58'
Sign on PP 2' west
This corner is located by GPS measurement

Corner History:

NO RECORDS

1853 Gov't Notes, William Jones; 40.0 set post and drove charred stake for 1/4 section corner. Built mound with trench and planted osage orange SE and apple seeds NE.

6-25-1964 J. Kerr found 1/2" x 6' steel rod with broken glass around it. In ground many years. Set CIM over 1/2"x4' rod. RPs- 120D in 12" boxelder W 46.65, MHD disc fence post WNW 32.6, MHD disc telephone pole NW 51.9.

8-3-1989 County Surveyor found C.I.M. corner is on East side of field drive North R.P.'s: C.S.D. in West side yard light pole N. 71.06. C.S.D. in P.P. # 38689 SW 2.33. C.S.D. in guide post # 38690 West 32.58. Main Center line field drive North West 14.0. Put sign on NE side P.P. # 38689.

8-16-2001 Mn/DOT survey crew found CIM in good condition.

10-7-2002 County Surveyor found CIM in good condition.

2-27-2004 County Surveyor found CIM down 0.7' in good condition. Set sign on new pp.