Certificate of Location of Government Corner

ID#: 632106 **Description:** 1/4 SEC COR 20 21 63 **Date Set:** 7/22/1964 **County:** Olmsted

Section: 21 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

18" Boxelder (tie taken midway between two spikes) N 9.76'
Minnesota Highway Disk in S side 45" Willow W 28.9'
County Survey Disk in W side blazed 13" Boxelder S 26.79'
Post w/sign 1' east
This corner is located by GPS reference stations "Big Shroom A & B"

Corner History:

1853 Gov't Notes, William Jones; 40.0 set post at 1/4 section corner and made trench. RP- 6" burr oak S76 E249.

5-1859 T. Hunter Pg.60 No.86; Used corner. Set 1/16 west.

10-1941 A. Armstrong; Set 1/4 corner with 3/4"iron rod. RPs- disc in willow east 30.2, disc in 24" elm SE 84.8'. Set 1/16 south.

9-1946 J.Kerr Bk.32 Pg.5; Found 3/4"x40" iron. 16 east set 3/4" pipe.

7-22-1964 J. Kerr set CIM over 1/2"x18" rod. RPs- lath 36" willow NE 38.35', lath 12" boulder N 9.85', lath 24" willow W 28.7', steel post E 1.0'. RR tie corner post moved to place CIM properly.

6-1989 County Surveyor found CIM at ground level in woods. Retook old ties- 18" boxelder 9.76' N(tie taken midway between two spikes), 45" willow 28.9' west (MHD in south face), 13" boxelder 26.79' S(CSD in blaze west face), post & sign 1.0' east.

8-5-2005 County Surveyor found CIM in good condition down 0.1'. Did not look for or check any ties.