Certificate of Location of Government Corner

ID#: 632305 **Description:** SEC COR 22 23 26 27 63 **Date Set:** 8/15/2005 **County:** Olmsted

Section: 23 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls in centerline of CR 123 south and east and in centerline of twp road north
County highway disk in PP #42435 W 34.39'
1/2" iron W 100.0'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones; 80.0 set post to corner of section 22-23-26-27. RPs- 12" burr oak N77 E79, 11" burr oak N76 W77, 13" burr oak S75 W205, 12" burr oak S61 E271.

5-1884 T. Hunter Pg.389 No.380; Found stone. 16 east set stone.

6-1892 T.Fraser Pg.492 No.466; Found stone.

5-1940 J.Kerr Bk.20 Pg.33; Found limestone. Set grey pointed boulder on top of limestone. 16 south set corner.

6-1951 J.Kerr Bk.51 Pg.68; Found boulder. Run line south and set 1/16 corner, run line east and set 1/16.

5-31-1962 J. Kerr set CIM over pipe. RPs- spike tele pole SE 86.6, spike tele pole NE 75.5', spike pp W 31.1', 1/2"x2' rod 1' south of fence west 100', bottle cap in new tele pole SE 93.4' (9-1970).

8-12-2005 County Surveyor found 1/2" pipe leaning south down 0.2' and removed. Found CIM down 1.4' in good condition.

8-15-2005 County Surveyor removed CIM and found 2"x6"x12" limestone down 3.2' in good condition and removed. Set 6' telspar pipe w/cast iron cap down 0.5'.