Certificate of Location of Government Corner

ID#: 632306 **Description:** 1/4 SEC COR 22 23 63 **Date Set:** 6/4/2008 **County:** Olmsted

Section: 23 **Township:** 106N **Range:** 13W **Monument Description:** 1" square pipe w/cap RLS #15809

Reference Ties:

The corner falls in centerline of N-S twp road and 12' south of centerline of field entrance east
County Survey Disk in E side PP SSW 80.88'
This corner is located by GPS reference stations "Cambridge A & B"

Corner History:

1853 Gov't Notes, William Jones; 40.0 set post of 1/4 section corner. Deposited charcoal, made mound and trench, pits, and planted cherry seeds NE & SW.

5-1884 T. Hunter Pg.389 No.38; found stone in center road . Set 16 east.

8-15-1969 J.Kerr; Found stone. Set CIM over limestone. RPs- beer cap in tele pole west side NE 48.6, pepsi cap in pp# 16064 SSW 194.5', most northerly of 2 rows of windbreak trees running E and W-meas. Centerline road S 152±.

8-27-1970 County Surveyor pulled CIM for grading. No monument in place.

1-14-2004 County Surveyor found RR spike down 0.3' in good condition.

8-12-2005 County Surveyor found RR spike down 0.3' in good condition.

8-7-2007 County Surveyor found RR spike down 0.3' in good condition. Removed spike and found nothing. Set 1/2" re-rod at RR spike location.

11-28-2007 County Surveyor found 1/2" rerod down 0.1' in good condition. Removed 1/2" rerod and found 3"x4"x12" limestone down 1.2' in good condition. Stone was 0.18' south and 0.22' east of 1/2" rerod.

6-4-2008 County Surveyor set 1" square pipe w/cap at surface at found stone location.