Certificate of Location of Government Corner

ID#: 632405 **Description:** SEC COR 23 24 25 26 63 **Date Set:** 5/8/2006 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 2' north of centerline of CR 123 and 1' west of centerline of Chester Rd SE
County highway disk in PP WNW 134.1'
County Survey Disk in NW side PP #43689 SW 50.93'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones; 80.0 set post at corner to section 23-24-25. Made mound, trench, and pits. Planted cherry seeds NE & SW, and plum seeds SE & NW.

6-1877 T. Hunter Pg.318 No.312; found remains of old stake in center road. Set boulder 6x10x15 in palce.

6-1901 R.Fraser Pg.706 No.620; found boulder in south track road, found meas. Correct.

1935 county highway department Bk.87 Pg,71; found stake on south side of boulder 1' below surface.

1940 J.Kerr Bk.20 Pg.33-34; Set or found stone at SW 25. RPs- hub SW 19.9', spike in tele pole # 117 NE 48.9', x in north end culv. NE 43.8'.

9-1962 J. Kerr found 2" pipe.

9-21-1963 J. Kerr set CIM over pipe at corner location.

8-1969 J. Kerr, RP left- disc in tele pole SE 44.4', disc in pp WNW 135.22', face of dead end sign. CIM 14" deep in new grade. Set 5/8"x11" rod riser when blacktopped. Will put in short CIM.

5-5-2006 County Surveyor found 5/8" rod down 0.7' in good condition.

5-8-2006 County Surveyor found rod down 0.7', took local ties and removed. Found CIM down 1.6', ties matched, removed. Found 2" pipe down 3.4', ties matched. Set 5/8"x1.1' rod over pipe down 2.2'. Set CIM down 0.4' over rod. CSD with concrete nail in NW side of PP #43689 SW 50.93'. Monument falls 2' north of centerline of 40th St and 1' west of Chester Road SE.
.