Certificate of Location of Government Corner

ID#: 632409 **Description:** SEC CEN 24 63 **Date Set:** 8/15/1969 **County:** Olmsted

Section: 24 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Monument

Reference Ties:

The corner falls in line with fence north, 1' south of E-W fence and 10' east of centerline of gully
Spike in 30" Burr Oak N 17.50'
Center 24" Burr Oak SSE 39'
Post w/sign 1' north
This corner is located by GPS reference stations "Noble A & B"

Corner History:

6-12-1901 R.Fraser Pg.706 No.620; Couldn't find stake in wash claimed set as corner. Set stone at inter lines. RPs- 10" burr oak S17°E 44 links, 8" burr oak N 66 3/4° 31 1/2 links.

8-15-1969 J.Kerr; found both bearing trees and stone. Set railroad spike in bed rock below CIM with original stones. RPs- S17° E 29' bark blazed toward corner, origianl bearing tree on level with corner, 20D in north side up 12" 20.96' N66 3/4° east record ok, 20" burr oak wraped in wires from old fences in fence line straight north across wash or gully, 40D on west side up 18" 17.52', corner lies just NW of ancient large corner post, old hydralic bumper jack about .45' east of corner up 8".

4-21-1976 McGhie & Betts found and used CIM.

8-8-1984 T. Ferguson found and used CIM.

1-23-1989 Roger Brand & Associates found and used CIM at center of section 24.

12-20-2001 Brand & Massey Surveying Inc. found and used CIM at center of section 24.

12-7-2005 Land Consultants found and used CIM.

9-11-2007 County Surveyor found CIM down 0.3' in good condition. Set post w/sign.