Certificate of Location of Government Corner

ID#: 632505 **Description:** SEC COR 25 26 35 36 63 **Date Set:** 7/7/1965 **County:** Olmsted

Section: 25 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls in line with fence east and in centerline of N-S twp road
+ in witness boulder W 33.0'
C and G bench mark SW 39.3'
Hub in PP SW 39.6'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes, William Jones; 80.0 set post of corner to section 25-26-35-36. Deposited charcoal, made trench, mound, and pits, and planted cherry seeds SE & SW. Plum seeds NE & NW.

4-1892 T.Fraser Pg.475 No.454; Corner gone. Set E-W point of N 1/4 36 by porp. Meas.

1935 county highway department Bk.87 Pg.71; Found boulder with cross on top, rotten stake on east side of stone. RPs- Tele pole SE 89.0', corner post SW 43.0'.

1940 J. Kerr Bk. 20 Pg. 33-34 used boulder w/cross as corner for measurements east.

7-7-1965 J. Kerr set CIM. RPs- Geological elevation bench monument SW 39.3', disc & nail in hub in pp SW 39.6', Corner lies in center old road traveled about 13' north of fence running east.

7-1982 Possibly could go ± 5' west or more(R.B.).

5-5-2006 County Surveyor found CIM down 0.6' in good condition.