Certificate of Location of Government Corner

ID#: 632506 **Description:** 1/4 SEC COR 25 26 63 **Date Set:** 5/20/1974 **County:** Olmsted

Section: 25 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Monument

Reference Ties:

The corner falls 24 1/2' north of FAI-90 R/W fence
County Survey Disk in NW side PP #6416 SW 39.28'
County Survey Disk in S side PP #34334 W 67.23'
This corner is located by GPS measurement

Corner History:

1853 Gov't Notes: William Jones, Deputy Surveyor North between sections 25 and 26. 40.00 chs. Set post at quarter section corner and deposited handful of charcoal and made mound, trench, and pits. Planted cherry seeds N.E. and S.W.

6-1901 Robert Fraser (P. 706), County Surveyor, states corner gone to bedrock and no corner ever found or set.

1940 John Kerr (Book 20 P. 33-34), County Surveyor, did not set corner or run line.

11-1961 MHD set 3/4" rod. RPs- State reference point in corner post W 32.32', State reference point in corner post E 27.90', State reference point in 4" plum NE 29.25'.

7-1965 John Kerr set 120d with hub midway and on line.

5-20-1974 County Surveyor found John Kerr's nail and hub destroyed in I-90 construction. Set a C.I.M. over a 1/2" x 20' rod midway and on line at 2631.61' by electronic traverse.

5-5-2006 County Surveyor found CIM down 0.2' in good condition.