Certificate of Location of Government Corner

ID#: 632609 **Description:** SEC CEN 26 63 **Date Set:** **County:** Olmsted

Section: 26 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.

County Surveyor recommends using the computed intersection of quarter lines for the center of section.

Reference Ties:

This corner is located by GPS reference stations "Plum Tree A & B"

Corner History:

6-1-1940 John Kerr, County Surveyor, (Kerr Field Book No. 20, Page 34) reset center with 4"x4"x17" stone with cross on top over stone. Built mound around stone.

6-6-1951 John Kerr, County Surveyor, (Kerr Field Book No. 51, Page 68) no mention of center. 1/16th West set iron midway and on line at 1317.1' to West 1/4. 1/16th Center of NW 1/4 set bridge bolt at intersecting sixteenth lines. 1/16th Center of SW 1/4 set iron at intersecting sixteenth lines.

1974 Pat Paterson found bridge bolt (could be John Kerr's center of section) down 1.5' and 3.8' north and 0.9' west of pipe by Thomas Taylor. Set many stones around bolt with 3/4" rod over bridge bolt. RPs - 1.2' north of north brace post and 8.2' north of south brace post.

12-20-1978 Yaggy Associates, Inc. used computed center at intersecting quarter lines.

4-26-2006 County Survey Crew found 5/8" pipe up 0.5' in good condition and measured its position using GPS. The corner falls 2' east of north-south fence near two plum tree/lilac bushes.

10-14-2010 County Survey Crew found 3/4" rod up 0.1' in good condition and measured its position using GPS.

3-23-2011 Joel Thoreson, County Surveyor, recommends using the computed intersection of quarter lines for the center of section. Based on the county's section breakdown, the 5/8" pipe, as located by GPS in 2006, falls 4.45' south and 1.00' east of the computed center and the 3/4" rod, as located by GPS in 2010, falls 0.56' south and 0.14' east of the computed center.

9-11-2017 G-Cubed used computed center at intersecting quarter lines.