Certificate of Location of Government Corner

ID#: 632709 **Description:** SEC CEN 27 63 **Date Set:** 9/13/2005 **County:** Olmsted

Section: 27 **Township:** 106N **Range:** 13W **Monument Description:** Note: Information regarding this center of section is provided for reference purposes only. A professional land surveyor should make the decision whether to use any existing survey monument or the computed intersection of quarter lines.
Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 18' west of centerline of N-S double PP line and 229' NE of FAI90 R/W fence
Post w/sign 1' north
This corner is located by GPS reference stations "Loeser A & B"

Corner History:

6-13-1892 T.Fraser Pg.492 No.466; Corner never set. Set 4x9x28 at true inter lines. 16 north set limestone.

5-31-1940 J.Kerr Bk.20 Pg.33; Found stone. 16 south set limestone.

1947 or 1948 J.Kerr Bk.35 Pg.38-39; Used corner and found 1/16 north stone.

6-1969 J.Kerr; found limestone and 1" iron pipe on west side. Corner considered permanent.

9-9-2005 County Surveyor found 2x9 stone up 0.3' in good condition with 1" pipe laying down on west side. The stone was found to be 0.13' West of computed intersection of quarter lines.

9-13-2005 County Surveyor removed 2x9x13 triangular stone and 1" pipe and set 6' telspar pipe w/cast iron cap down 0.2' at intersecting quarter lines.