Certificate of Location of Government Corner

ID#: 633004 **Description:** 1/4 SEC COR 30 31 63 **Date Set:** 11/1/2006 **County:** Olmsted

Section: 30 **Township:** 106N **Range:** 13W **Monument Description:** Cast Iron Cap on telspar pipe

Reference Ties:

The corner falls 0.3' east of east face of CP to fences E-W-N
Post w/sign 1' east
This corner is located by GPS reference stations "Rawson A & B"

Corner History:

1853 Gov't Notes; William A. Jones, Deputy Surveyor east on true line between sections 30 & 31. 38.71 chs. Set post at quarter section corner. 78.71 chs to section corner.

7-1857 Thomas Hunter (Pg 35, No. 56) County Surveyor used the corner to set the 1/16 West.

7-1977 The County Surveyor dug at the corner post for the corner and didn't find anything.

8-2-1977 The County Surveyor set a Cast Iron Cap on a 4' long square pipe as the corner on the line from the south 1/4 corner 31 over the Center 31 (a stone found) and in line with the E-W fence. The corner came 1 1/2' West of the corner post to the fences N-S-E-W.

6-11-1987 Vince Fangman set 1/2" pipe w/cap #14888 as corner in City of Rochester flood control survey.

9-13-1989 County Surveyor found 1/2" pipe/cap #14888 0.28' east of east edge of new corner post in line with E-W fence. Fence also north.

10-31-2006 County Surveyor found 1/2" pipe w/cap RLS #14888 down 0.2' in good condition.

11-1-2006 County Surveyor removed 1/2" pipe w/cap and set 4 1/2' telspar pipe w/cast iron cap at surface. Set post w/sign.